

PSSnet GW1 MOD-CAN

311602



PSSnet, gateway, protocol converter between ModBus/TCP and CANopen, supports CiA 301 V4.2.0, for use with PSS controllers, PMI, PMCprimo, RJ45 port, 9-pin D-Sub plug-in connector, supply voltage 24 V DC, buffer 20 ms.

Technical details

General data	
Approval:	CE, cULus Listed
Technical data	
Electrical data	
Purpose of U1:	Module supply
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	3 W
Fieldbus interface	
Fieldbus interface:	CANopen
Fieldbus device type:	Slave
Name of fieldbus protocol:	CiA 301 V4.2.0
Perm. fieldbus station address:	0 - 99d
Selectable transmission rates:	10 kBit/s, 500 kBit/s, 20 kBit/s, 250 kBit/s, 1 MBit/s, 800 kBit/s, 50 kBit/s, 125 kBit/s
Connection fieldbus:	9-pin D-Sub male connector
Galv. isolation fieldbus:	Yes
Type of galvanic isolation:	Functional insulation
MODBUS	
Number of MODBUS interfaces:	8
Modbus connection:	RJ45

Modbus device type:	Server
Modbus operating modes:	Auto-MDIX, Autonegotiation
Modbus selectable trans. rate:	10 MBit/s, 100 MBit/s
Galv. isolation from Modbus:	Yes
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Potential separation	
Potential isolation 1 between:	CANopen and system voltage
Type of potential isolation 1:	Functional insulation
Potential isolation 2 between:	Modbus and system voltage
Type of potential isolation 2:	Functional insulation
Mechanical data	
DIN-rail dimensions:	35 x 7.5 EN 50022
Housing material lower section:	PC
Housing material front plate:	PC
Connection terminal:	Screw terminal plug-in, Spring-loaded terminal, plugin

Flex. cond. c/s AWG info:	24 - 12 AWG
Height dimension:	96 mm
Width dimension:	22.5 mm
Depth dimension:	114.3 mm
Net weight:	90 g
Gross weight:	110 g
Environment	
RoHS conformity:	yes
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	6 small IT-/communic. device
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27242208
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000024

Obligatory accessories



783542

Spring terminals PNOZ mmcxp, 1 pc.



793542

Screw terminals PNOZ mmcxp, 1 pc.