

## PSSnet SHL 6T 2FSMSC MRP

380650



Industrial Ethernet Switch, managed, 6 x standard 10/100 BASE TX, RJ45, 2 x 100BASE-FX singlemode SC ports, ring redundancy MRP.

## Technical details

### General data

Approval: CE, cULus Listed

### Technical data

### Electrical data

Supply voltage (V): 10 - 10 V

Type of supply voltage U1: DC

### Environmental data

Ambient temperature: 0 - 60 °C

Humidity rating: 95 % r. h. at 40 °C

EMC to standard ...: EN 55022 Class A, EN 61000-4-4, FCC CFR47 Part 15 Class A, EN 61000-4-5, EN 61000-4-6, EN 61000-4-2, EN 61000-4-3

Vibration to standard ...: EN 60068-2-6

Acc. shock to standard1: 15g

Pollution degree clear.&creep.: 2

### Mechanical data

Height dimension: 131 mm

Width dimension: 74 mm

Depth dimension: 111 mm

Net weight: 429 g

Gross weight: 760 g

### Environment

WEEE klassifikation (08/2018):	6 small IT-/communic. device
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	19170106
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000037

## Optional accessories



380000

SafetyNET p Cable per mtr



380400

SafetyNET p Connector RJ45s