

PIT js2

401100



PITjog manually operated control device 3 built-in pushbuttons, connection via 10-pin coiled cable with open end.

Technical details

General data	
Approval:	CE
Self-monitored:	no
Technical data	
Electrical data	
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	AC/DC
Push button	
Number, pushbutton:	3
Relay outputs	
Voltage DC1 safety cont.:	24 V
Environmental data	
Ambient temperature:	-10 - 55 °C
Mechanical data	
Length cable:	5 m
Material of cable insulation 1:	PUR
Conductor cross section:	0.14 - 0.14 mm ²
Housing material:	PC-ABS-Blend UL 94V0
Height dimension:	341 mm
Width dimension:	75 mm

Depth dimension:	60 mm
Net weight:	837 g
Gross weight:	951 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27371244
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000017