

Enabling switch, 3 levels, 1 signal contact, 6-core cable (5 m) with open end.



## Technical details

### General data

Approval: CE

Self-monitored: no

### Technical data

#### Relay outputs

Utilisation cat. AC15/DC13sta.: EN 60947-5-1

Voltage AC15 safety cont.: 125 V

Max. current AC15 safety cont.: 0.3 A

Voltage DC13 safety cont.: 30 V

Max. current DC12 safety cont.: 1 A

### Environmental data

Ambient temperature: 0 - 50 °C

### Mechanical data

Length cable: 5 m

Material of cable insulation 1: PUR

Mounting position: any

Connection type: 5 m cable

Housing material lower section: PP

Height dimension: 125 mm

Width dimension: 45 mm

Depth dimension:	45 mm
Diameter:	45 mm
Net weight:	361 g
Gross weight:	388 g
<b>Environment</b>	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27371238
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000026