

PMCTendo DD4.10/162/230-480V

4105618



Servo amplifier; Technical data at 3 x 400 V AC: Continuous output current: 10 A; I_{max} (5 s) = 20 A; Power consumption in S1 mode: 7 kVA Integral brake resistor incl. relay AS (restart interlock).

Technical details

| | |
|--------------------------------|------------------|
| General data | |
| Approval: | CE, cULus Listed |
| Technical data | |
| Electrical data | |
| Purpose of U1: | Mains supply |
| Supply voltage (V): | 230 - 230 V |
| Type of supply voltage U1: | AC |
| Purpose of U2: | supply |
| Supply voltage 2 (V): | 24 - 24 V |
| Type of supply voltage U2: | DC |
| Power section | |
| Peak current for 5 s: | 20 A |
| Analog inputs | |
| Number of analogue inputs: | 2 |
| Type of analogue inputs: | Voltage |
| Resolution of analogue inputs: | 14 Bit, 12 Bit |
| Inputs | |
| U input to EN 61131-2 Type 1: | 24 V DC |
| Analogue outputs | |
| Number of analogue outputs: | 2 |

| | |
|--------------------------------|------------------------------|
| Type of analogue outputs: | Voltage |
| Resolution, analogue outputs: | 10 Bit |
| CANopen interface | |
| Number of CANopen interfaces: | 1 |
| Serial interface | |
| Number of RS 232 interfaces: | 1 |
| Mechanical data | |
| Height dimension: | 325 mm |
| Width dimension: | 70 mm |
| Depth dimension: | 265 mm |
| Net weight: | 6000 g |
| Gross weight: | 6000 g |
| Environment | |
| RoHS conformity: | yes |
| REACH compliance: | Contains no SVHC substances |
| WEEE classification (08/2018): | 5 devices (feed size < 50cm) |
| Commercial data | |
| ECLASS version: | ECLASS-9.1 |
| ECLASS Reference Feature: | 27023201 |
| ETIM Version: | ETIM-7.0 |