

PSEN cs1.19n/PSEN cs1.19 1sw/3actuators

540303

RFID safety switch, 2 safe SC outputs, 5-pin M12 male connector, one actuation direction, IP67, typ. operating distance 11 mm, Sao = 8mm, Sar = 20 mm, PU = 1 piece coded switch with three actuators (OSSD1 &2, OSSD1, OSSD2).



Technical details

General data	
Approval:	CE, cULus Listed, FCC, IC, TÜV, EAC (Eurasian)
Sensor principle:	Transponder
Coding level to ISO 14119:	Low
Classification to EN 60947-5-3:	PDDb
Transponder coding:	coded
Suitable for series connection:	no
unit type:	Unit
Technical data	
Electrical data	
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	2 W
Semiconductor outputs	
Number of OSSD outputs:	2
Potential isolation S/C O:	No
S/C output short circuit proof:	Yes
Utilisation cat. to EN 60947-1:	DC-12
Environmental data	
Ambient temperature standard:	EN 60068-2-14

Ambient temperature:	-25 - 55 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
EMC to standard ...:	EN 60947-5-3
Vibration to standard ...:	EN 60947-5-2
Acc. shock to standard1:	30g
Overvoltage category:	III
Pollution degree clear.&creep.:	3
Switching distances	
Change op. dist. temp.change:	+0.01mm/°C
Mechanical data	
Type 1 actuator:	PSEN cs1.19
Sensor can be flush-mounted:	Yes, follow installation guide
Connection type:	M12, 5-pin male
Housing material upper part:	PBT
Height dimension:	75 mm
Width dimension:	40 mm
Depth dimension:	40 mm
Net weight:	190 g
Gross weight:	239 g
Transponder	
Operating frequency:	122 kHz - 128 kHz
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)

Commercial data

ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27272403
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000026

Optional accessories



380209

PSS67 Cable M12sf M12sm, 5m



540311

PSEN screw M5x10 10pcs



540312

PSEN screw M5x20 10pcs



630347

PSEN op cable angle M12 5-pole 3m



630311

PSEN op cable axial M12 5-pole 5m



630312

PSEN op cable axial M12 5-pole 10m



630348

PSEN op cable angle M12 5-pole 5m



630349

PSEN op cable angle M12 5-pole 10m



630350

PSEN op cable angle M12 5-pole 30m



380210

PSS67 Cable M12sf M12sm, 10m



630298

PSEN cable M12-5sf 20m



380211

PSS67 Cable M12sf M12sm, 30m



630310

PSEN op cable axial M12 5-pole 3m



380220

PSS67 cable M12-5sf, M12-5sm, 20m



630297

PSEN op cable axial M12 5-pole 30m



380214

PSS67 Cable M12af M12am, 10m



380215

PSS67 Cable M12af M12am, 30m



380212

PSS67 Cable M12af M12am, 3m



773600

PDP67 F 8DI ION



380213

PSS67 Cable M12af M12am, 5m



380208

PSS67 Cable M12sf M12sm, 3m
