

Controller Cylindrical Type Socket

■ Cylindrical type socket(8 Pin, 11 Pin)

(unit: mm)

Model	Socket	
	PG-08	PG-11
Appearances & Dimensions		
	<p>PG-08 dimensions: 38 (width), 9 (pin spacing), 31 (height), 41 (total height), 21 (depth), 16 (base width), $\varnothing 25$ (hole diameter).</p> <p>PG-11 dimensions: 45 (width), 8.5 (pin spacing), 33 (height), 43.5 (total height), 5 (depth), 21 (total depth), 16 (base width), $\varnothing 27$ (hole diameter).</p>	

Model	Socket	
	PS-08	PS-11
Appearances & Dimensions		
	<p>PS-08 dimensions: 50 (width), 40 (pin spacing), 70 (height), 4 (base thickness), 23.5 (depth), 19 (total depth), 14 (base width), 35 (total height), 2-$\varnothing 4.5$ (mounting holes).</p> <p>PS-11 dimensions: 50 (width), 40 (pin spacing), 70 (height), 4 (base thickness), 31 (depth), 29.5 (total depth), 24.5 (base width), 35 (total height), 2-$\varnothing 4.5$ (mounting holes).</p>	

Model	Socket	Adaptor	Bracket
	PS-M8	Beige(FGB48-GR) / Black(FGB48-BL)	PGB48-W
Appearances & Dimensions			
	<p>PS-M8 dimensions: 41 (width), 33 (pin spacing), 64 (height), 3.5 (base thickness), 20 (depth), 19 (total depth), 14 (base width), 35 (total height), 2-$\varnothing 4.5$ (mounting holes).</p> <p>Adaptor dimensions: 58 (width), 76 (height), 88 (total height), 45 (inner width), 2-$\varnothing 4.5$ (mounting holes).</p> <p>Bracket dimensions: 7 (thickness).</p>		
	<p>※ Only for ATS8 Series socket.</p> <p>※ ATE Series Bracket is sold separately.</p>		

- (A) Photo electric sensor
- (B) Fiber optic sensor
- (C) Door/Area sensor
- (D) Proximity sensor
- (E) Pressure sensor
- (F) Rotary encoder
- (G) Connector/Socket
- (H) Temp. controller
- (I) SSR/ Power controller
- (J) Counter
- (K) Timer
- (L) Panel meter
- (M) Tacho/ Speed/ Pulse meter
- (N) Display unit
- (O) Sensor controller
- (P) Switching mode power supply
- (Q) Stepper motor& Driver&Controller
- (R) Graphic/ Logic panel
- (S) Field network device
- (T) Software
- (U) Other