Ø30 Round Push Button Switches (S3PR Series)

-	Appearance		Contact block		LED block		
Туре		Model	A contact	B contact	AC/DC voltage	AC voltage	
Extended		S3PR-P1 □A(M)	1	_			
		S3PR-P1 [2A(M)	2	-			
	S3PR-P1R□	S3PR-P1 []3A(M)	3	-			
		S3PR-P1 B(M)	-	1			
		S3PR-P1 ² B(M)	-	2]_	_	
		S3PR-P1 []3B(M)	-	3	_		
		S3PR-P1 AB(M)	1	1			
		S3PR-P1 2AB(M)	2	1			
		S3PR-P1 A2B(M)	1	2			
		 ※□ indicates color : ■, ■, □, Y, X ※ The M in the model name indicates modular type contact block. Models without M are singular contact block. ※ The control unit, contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters) 					
		Dimensions				(unit: mm)	
		189 30.4		hickness: Max. 6mm	Singular typ Modular typ	e 48.5 25.0	
_				anel cut-out dime		er to page A-105.	
			Contact block		LED block		
Туре	Appearance	Model		B contact		AC voltage	
	Appearance		A contact	B contact	AC/DC voltage	AC voltage	
Type Flush	Appearance	S3PF-P1□A(M)	A contact 1	B contact		AC voltage	
	Appearance	S3PF-P1 □A(M) S3PF-P1 □2A(M)	A contact 1 2	B contact		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M)	A contact 1	- - -		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□B(M)	A contact 1 2 3 	 1		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□B(M) S3PF-P1□2B(M)	A contact 1 2	 1 2		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□B(M) S3PF-P1□3B(M)	A contact 1 2 3	 1 2 3		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□2B(M) S3PF-P1□3B(M) S3PF-P1□AB(M)	A contact 1 2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	 1 2		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□B(M) S3PF-P1□3B(M)	A contact 1 2 3	 1 2 3 1		AC voltage	
	Appearance	S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□3A(M) S3PF-P1□3B(M) S3PF-P1□3B(M) S3PF-P1□3B(M) S3PF-P1□2AB(M) S3PF-P1□2AB(M) S3PF-P1□2AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) X□nidicates color : ■, ■, ■, ■ X□nidicates color : ■, ■, ■	A contact 1 2 3 1 1 2 1 1 2 1 . Y, K dicates modular t cks, LED blocks a	1 2 3 1 1 2 3 1 1 2 ype contact block are sold separately	AC/DC voltage	_	
		S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□2B(M) S3PF-P1□3B(M) S3PF-P1□3B(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□ACB(M) ※□ indicates color : ■, ■, ■ ※□ indicates color : ■, ■, ■ wThe M in the model name in contact block. % The Control unit, contact block.	A contact 1 2 3 1 1 2 1 1 2 1 therefore the second s	 1 2 3 1 1 2 ype contact block are sold separately ar letters)	AC/DC voltage	_	
		S3PF-P1□A(M) S3PF-P1□2A(M) S3PF-P1□3A(M) S3PF-P1□3A(M) S3PF-P1□3B(M) S3PF-P1□3B(M) S3PF-P1□3B(M) S3PF-P1□2AB(M) S3PF-P1□2AB(M) S3PF-P1□2AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) S3PF-P1□AB(M) X□nidicates color : ■, ■, ■, ■ X□nidicates color : ■, ■, ■	A contact 1 2 3 1 2 1 2 1 1 2 1 1 2 1 1 2 1 1 cks, LED blocks a ontact block: regula		AC/DC voltage	A are singular (unit: mm) (unit: mm)	



Ø30 Push Button Switches

				Contact block		LED block		
Гуре	Appearance		Model	A contact	B contact	AC/DC voltage	AC voltage	
Flush			S3PF(U)-P3 ADM	1	_	ji terze tentige		
illuminated)			S3PF(U)-P3 ² 2ADM	2	_	_		
			S3PF(U)-P3DBDM	_	1	1		
		act	S3PF(U)-P3 2BDM		2			
		Modular contact	S3PF(U)-P3DABDM	1	1	_		
		arc	. ,	1	1			
		Inpo	S3PF(U)-P3 ALM	2	-	_		
		Σ	S3PF(U)-P3 2ALM	2	1	_	1	
				-	1		1	
			S3PF(U)-P3 2BLM	-	2	-		
			S3PF(U)-P3 ABLM indicates color: R, B, G, Y,	1	1			
	S3PFU-P3G	(cc %Cc %Mc ma %Th	 The control unit, contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters) Control unit+contact block (modular type) models do not contain "Push" markings on the button cap. Models with 'U' in the model name is available only for control unit. 'U' models do not contain "Push" markings on the button cap. The LED color is the same as the control unit. Waterproof cap (model: SA-WP) is available. Dimensions 					
				Panel thickness:	Max. 6mm		(unit: mm)	
		48.1	30.4 3.4	57.8	4 ⁶ 66			
			※For panel cut-out dimensions, please refer to page A					
	Appearance		Model	Contact block		LED block	1	
				A contact	B contact	AC/DC voltage	AC voltage	
			S3PF(U)-P3 AD	1	-	_	_	
			S3PF(U)-P3□2AD	2				
		t	S3PF(U)-P3DBD	-	1	1		
		contact	S3PF(U)-P3 ² 2BD	-	2	_		
			S3PF(U)-P3□ABD	1	1			
		Singular o	S3PF(U)-P3 AL	1	-	_		
		Sin	S3PF(U)-P3 ² 2AL	2	-	4		
			S3PF(U)-P3DBL	-	1		1	
			S3PF(U)-P3 ² 2BL	-	2	_		
	S3PF-P3G		S3PF(U)-P3DABL	1	1			
		 Indicates color: R. S. Y. W The control unit, contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters) Control unit+contact block (singular type) models contain "Push" markings on the button cap. Models with 'U' in the model name is available only for control unit. 'U' models do not contain "Push" markings on the button cap. The LED color is the same as the control unit. 'Waterproof cap (model: SA-WP) is available. 						
		• Din	Dimensions Panel thickness: Max. 6mm (unit: mr					
			481			39.4		



ular

ular

ular

-head

(unit: mm)							
Туре		A	В	Panel Cut-out Dimensions	ø30		
Round Push Button Switches (S3PR/S3PF Series)			45	55	nat n±0.5	Dan Button Switches	
Round Selector Switches	Short lever		37	55	Min. A ^{±0.5} Ø30.5	Round Square Rectangular	
(S3SF/S3SFN Series)	Long lever		55	55		Selector Switches Round Square	
Round Key Selector Switches (S3KF Series)		37	55		Rectangular Key Selector Switches Round		
Pilot Lights (L3RF Series)		37	55		Square		

Double Push Button Switches Mushroom-head Push Button Switches

Ø16

Emergency Switches

t Lights

Accessories

Buzzers